



Joe H65 / H75

design Midj R&D, 2015

Stool with four legs base in lacquered steel. Seat and backrest upholstered in fabric, leather, ecoleather, hide or regenerated hide. The backrest is available with front face upholstered and back in veneered wood, or wooden seat and backrest.



Finishing and Materials

Structure



White Steel



Sand Steel



Grafite Steel

Coating



Mirage Fabric
16 colors



Long Life Fabric
13 colors



Natural Wool Fabric
15 colors



Bubble fabric
14 colors



Hot Fabric
13 colors



Pix Fabric
13 colors



Inca Ecoleather
17 colors



Magic Ecoleather
17 colors



Vintage Ecoleather
4 colors



Special Leather
8 colors



Fiore Leather
15 colors




Vintage Leather
4 colors



Rigenerated Hide
10 colors



Hide
19 colors



Stained wood Natural Oak
finish




Stained wood Dark Oak
finish



Stained wood Flamed
Walnut finish

Dimensions



Volumetric Details

Weight 7.5

Volume 0.28 mc

Package 1

Dimension	cm	inch
A	98/108	38.6/42.5
B	44	17.3
C	52	20.5
D	66/76	26/29.9

Gallery



Materials Certifications

Mirage Fabric

Martindale: 100.000 cycles Composition: 100% Polyester Shrinking about 1% Fire retardant fabric: classe 11M, B1 DIN 4102, M1, B1 OENORM Part.1, BS 5852 Crib 5, EN 1021, USA Calif. Bull 117, IMO 688 (17) - IMO 563 (14) - IMO 653 (16)

Long Life Fabric

Martindale 40.000 cycles Composition: 74% Polyester, 18% Cotton, 8% Acrylic Shrinking about 1%

Natural Wool Fabric

Martindale: 100.000 cycles Composition: 70% Wool, 25% Polyamid, 5% Fibers Shrinking about: 1% Fire retardant fabric: BS 5852 part. 1, Cigaret test, Match test

Bubble fabric

Martindale: 35.000 cycles Composition: 100% Pes Fire retardant fabric: BS5852:2006 (p. 11 CRIB 5), EN1021-1, EN1021-2, UNI 9175:2010 - classe 1 im

Hot Fabric

Martindale: 45.000 cycles Composition: 100% Pes Fire retardant fabric: BS5852:2006 (p. 11 CRIB 5), EN1021-1, EN1021-2, UNI 9175:2010 - classe 1 im

Inca Ecoleather

Martindale: 50.000 cycles Composition: 6% Cotton, 6% Polyester, 88% PVC Shrinking about: 1% Fire retardant fabric: Classe 11M, BS 5852 Part. 1, IMO RES. A.652(16)

Magic Ecoleather

Martindale: 150.000 cycles Composition: 31% Cotton, 48% Polyurethane, 21% Polyester Shrinking about: 1% Fire retardant ecoleather: Classe 11M, BS 5852 Part. 1, Cigaret Test, Match Test

Vintage Ecoleather

Ecoleather phtalatic free - R.E.A.C.H. 1907/2006/EU Breathable ecoleather Composition: 90% PVC, 7% Polyurethane, 3% Cotton Shrinking about 1%

Fiore Leather

BS 5852 parte 1; ISO 5402>50000 cicli; ISO 105B02 ? 5; ISO 3377-1 ?20 N; ISO 11644 ? 2.5 N/Cm; EN 1021/1-2; EN ISO 17233 -20°; IMO RES A 6528(16)

Vintage Leather

UNI EN ISO 105 B02 ?3; ISO 5402>50000 cicli; ISO 3377-1?20; UNI EN ISO 11640 Secco - Dry 50 c ? 4 Umido - Wet 20 c ? 3; Sudore - Sweat 20 c ? 3