



Utförande: Lackerad aluminium. Vrid- och vinklingsbar. Vit RAL 9016.

Svart NCS S9000. Ljusgrå RAL 7030. Olivgrön RAL 6003.

LED info: Systemeffekt 17W. Armaturlumen se nedan. Korrelerad färgtemperatur 4000K. (3000K på förfrågan) Färgtolerans SDCM 3.

Färgåtergivning >RA 80.

Montage: I tak eller på vägg.

Anslutning: Kopplingsplint.

Design: Jens Fager 2017

W	SPRIDNING/BEAM	ART.
LED1325LM/17W	18°	8400-1-XX
LED1325LM/17W	18°	8400-1-XXHFF
LED1250LM/17W	24°	8401-1-XX
LED1250LM/17W	24°	8401-1-XXHFF
LED1310LM/17W	54°	8401-1-XX
LED1310LM/17W	54°	8401-1-XXHFF

XX = -01 Vit/White, -06 Svart/Black, -11 Grå/Grey, -12 Grön/Green

HFF = Dimmbart DALI alt. SwitchDim/Dimmable DALI or SwitchDim

Finish: Painted aluminum. White RAL 9016, Black NCS S9000, Grey RAL 7030, Green RAL 7022. Other colours on request. Adjustable.

LED info: System power 17W. Luminaire Luminous Flux see above. CCT 4000K. (3000K on request) SDCM 3. CRI >80.

Mounting: In ceiling or on wall.

Connection: Terminalblock.

Design: Jens Fager 2017



