



SP URBA PI

Design by Dima Loginoff

Collection consisting of aluminium ceiling lamps and suspended lamps.
Available in several colours and sizes.


Typology: RECESSED SUSPENSION LAMP

Ratings

- Built in line voltage **LED** module
- CCT 3000 K
- Downlight
- Ceiling cut-out installation
- Supply voltage ~220-240V
- Switch mode: on-off, dimmable trailing edge
- Die cast aluminium body, painted
- Opalescent diffuser

kg 1,7 m³ 0,02

Product code composition



URBAN / solo con illuminazione verso il basso / downward lighting only

Type	Article	Colours	Finishing	Source
SP	URBA P I	BC wrinkled white	XX	LED 15W - diffused beam 3000K available on request 2700K or 4000K
		BR matt bronze		
		NI matt nickel		

CE IP20 CRI90 220-240VAC **LED** ~1350 lm 90 lm/W

foro - hole Ø 4,5 cm / profondità min - min depth 10 cm

example composition code | SP | URBAPI | BC | XX | LED

Available colors



BC
Wrinkled
white



BR
Matt
bronze



NI
Matt
nickel

EELc (Energy Efficiency Label compatibility) contain built in LED lamps that cannot be changed: A, A+, A++

SPURBAPI _ _ XXLED

CUSTOMER _____ NOTES _____

Luminous flux (lm) and efficacy (lm/W) for all built in LED luminaires is based on nominal ratings of the LED sources.
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.