



PLURBMIP
Design by Dima Loginoff

Collection consisting of aluminium ceiling lamps and suspended lamps.
Available in several colours and sizes

Typology: CEILING


Ratings

- Built in line voltage **LED** module
- CCT 3000 K
- Downlight
- Surface installation over holes
- Supply voltage ~220-240V
- Switch mode: on-off, dimmable trailing edge
- Aluminium body, painted
- Diffuser

Product code composition

URBAN MINI

Type	Article	Colours	Finishing	Source
PL	URB MI P	BC wrinkled white	XX	LED 8W - diffused beam 3000K available on request 2700K or 4000K
		BR matt bronze		
		NI matt nickel		



IP20 CRI90 220-240VAc **LED** ~560 lm 70 lm/W
 example composition code | PL | **URBMIP** | BR | XX | **LED**

Available colors



BC
Wrinkled white

BR
Matt bronze

NI
Matt nickel

EELc (Energy Efficiency Label compatibility) contain built in LED lamps that cannot be changed: A, A+, A++

PLURBMIP _ _ XXLED

CUSTOMER _____

NOTES _____

NOTICE:

Luminous flux (lm) and efficacy (lm/W) for all LED luminaires is based on nominal ratings of the LED sources.
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.